

Bildal Product Specifications Table

Type	Wattage (Watts)	Primary Amps.	Min. PF	Min. Eff (%)	Secondary Full Load A	Secondary Short Circuit A	Load Ohms	Max Open Circuit V (RMS)	Catalogue No
B331-1	30/45	6.6	0.95	80	6.53-6.67	6.6-7.1	1.15	25	BE045665
B331-2	30/45	20.0	0.95	80	6.53-6.67	6.6-7.1	1.15	25	BE045204
B331-3	65	6.6	0.95	80	6.53-6.67	6.6-7.1	1.60	30	BE065662
B331-4	100	6.6	0.95	85	6.53-6.67	6.6-7.1	2.44	70	BE100667
B331-5	100	20.0	0.95	85	6.53-6.67	6.6-7.1	2.44	70	BE100668
B331-6	200	6.6	0.95	90	6.53-6.67	6.6-7.1	4.82	100	BE200661
B331-7	200	20.0	0.95	90	6.53-6.67	6.6-7.1	4.82	100	BE200201
B331-10	300	6.6	0.95	90	6.53-6.67	6.6-7.1	8.25	135	BE300661
B331-11	300	20.0	0.95	90	6.53-6.67	6.6-7.1	8.25	135	BE300201
B331-16	10/15	6.6	0.95	70	6.53-6.67	6.6-7.1	0.34	8.0	BE015661
B331-17	20/25	6.6	0.95	70	6.53-6.67	6.6-7.1	0.57	8.0	BE025662
B331-18	150	6.6	0.95	85	6.53-6.67	6.6-7.1	3.58	70	BE150669
B331-19	150	20.0	0.95	85	6.53-6.67	6.6-7.1	3.58	70	BE150201
B5A/143	45	8.3	0.95	85	6.53-6.67	6.6-6.95	1.15	13.6	BE045833
B5A/142	65	8.3	0.95	85	6.53-6.67	6.6-6.95	1.60	19.6	BE065836
B5A/141	200	8.3	0.95	90	6.53-6.67	6.6-6.95	4.82	60.8	BE200831
	15	20	0.95	70	6.53-6.67	6.6-7.1	0.34	8.0	BE015202